NBIA 5.0

Local Installation Guide







Center for Biomedical Informatics and Information Technology

Revised December 16, 2010

Table of Contents

INTRODUCTION	1
NBIA 5.0 SOFTWARE AND TECHNOLOGY REQUIREMENTS	2
Java SDK Installation	3
Apache Ant Installation Apache Ant Environment Variables	 3 3
MySQL Installation and Configuration	6
DOWNLOADING AND INSTALLING UPT	8
INSTALLING NBIA 5.0 APPLICATION AND SERVICES	8
Downloading NBIA 5.0 files	9
Installing a New NBIA 5.0 GUI Installer Method of Installation	10 10
Installing NBIA One Component at a Time	22
Command-Line Method of Installation About Properties	23 23
Command-line Installation Steps	25
Upgrading NBIA 4.5 to 5.0 Upgrading NBIA Using the GUI Installer Upgrading NBIA Using Command-Line Installer	29 30 32
Configuring JBoss Configuring JBoss Servers and MySQL Server to Run as Services	33 34
POST-INSTALLATION TASKS Using UPT to Add NBIA Users	36 36
CONTACTING APPLICATION SUPPORT	38

Introduction

This *NBIA 5.0 Installation Guide* provides you with the instructions to install and configure a fresh NBIA 5.0 application, or upgrade an existing 4.5.x application. The NBIA installation installs and configures two JBoss application servers and creates a NBIA-specific schema within a pre-existing database on a preinstalled MySQL server. NBIA supports both Oracle and MySQL. An upgrade of NBIA converts an existing 4.5.x NBIA application and associated grid service to 5.0.

Directions are given in this document for both Linux and Windows operating systems.

Overview of NBIA Installation	 The process for installing NBIA includes the following tasks described in this document: 1. Downloading and installing required software 2. Setting environment variables 3. Downloading NBIA 5.0 distribution files 4. Installing NBIA: a. GUI Installer Method b. Command-Line Method Editing install.properties file 5. Upgrading NBIA a. GUI Installer Method b. Command-Line Method command-Line Method 6. Configuring JBoss servers and MySQLserver to run as a service 7. Post-Installation Tasks a. Using UPT to Add NBIA Users
-	
Before You Proceed	If you have a 3.x version of NBIA installed, you must do a fresh installation as there is no way to upgrade a 3.x NBIA installation to 4.x. Contact NCICB Application Support directly for 3.x data migration support:
	Web: http://ncicb.nci.nih.gov/NCICB/support E-mail: ncicb@pop.nci.nih.gov Telephone: 301-451-4384 Toll free: 888-478-4423

NBIA 5.0 Software and Technology Requirements

Tested Environment	The NBIA 5.0 installation has been tested on Linux Red Hat Enterprise Linux AS 4 64/32-bit (for AMD chipset) and the Windows XP/2003 environments. While the installation may work in other Linux and Windows environments, it has only been tested in these environments.
Minimal Requirement	The system requirement varies according to the capacity the system is planned for, such as concurrent users, number of images, etc.
Environment	OS Windows or Linux server CPU – Intel 64-bit Core Duo processor or AMD Opteron HD – 160 GB SATA HD RAM – 3GB
Required Software—Not Included in NBIA	Many of the servers and services that make up NBIA 5.0 are automatically installed as part of this installation. However, there are certain tools that you must manually install and configure. These tools are listed in Table 1. The software name, version, description, and URL hyperlinks (for download) are indicated in the table.

Prior to the NBIA 5.0 installation, you must download and install the following tools and recommended versions in the order they are listed in Table 1. Complete the directions for installing each, as directed on the corresponding website.

Required Software Name	Description
Version	Description
Java 2 Platform Standard Edition 6.0 Update 18(J2SE 6.0)	The J2SE Development Kit
http://java.sun.com/products/archive/j2se/6u18/index.html	(JDK) supports creating J2SE applications.
Be sure to download the correct Java SDK for your operating environment. For example, for Linux AMD 64, you would download jdk- 1_6_0_18-linux-amd64-rpm.bin. For Windows, you might download jdk-1_6_0_18-windows-i586-p.exe.	
Apache Ant, 1.7.0	Apache Ant is a Java-based
https://gforge.nci.nih.gov/svnroot/lsd/trunk/tools/apache-ant-1.7.0-bin.zip	build tool.
MySQL, 5.0.45 or Oracle, 10g	MySQL is an open-source
http://downloads.mysql.com/archives.php?p=mysql-5.0&v=5.0.45	database software application.
	Oracle is a commercial database product that must be purchased.

Table 1Required Software



As you install each application, record the installation directory path, and the hostname of your MySQL DB server, and the DB admin username/password.

Java SDK Installation

When you install the Java SDK, you are prompted to select the installation directory. Record the path, as this directory will be used when you set the environment variables.

Apache Ant Installation

- Unzip the Apache Ant distribution files using a command line unzip tool or a zip utility, such as WinZip.
- After extracting the zip, you must set the environment variables, described in the following section, so that Ant is available in the system PATH.

Apache Ant Environment Variables



The purpose of setting operating system environment variables is so that the Java SDK and Ant build tool are available to run from anywhere in the system.

Linux

To set the environmental variables in Linux, follow these steps:



The JAVA_HOME, ANT_HOME and PATH environment variables are set in /etc/profile. You may need to create the variables, or modify them if they already exist.

Step	Action
1	As the root user, enter the following in the /etc/profile file. A PATH variable should already be created in this file, so be sure to define the JAVA_HOME and ANT_HOME export before the PATH export. Replace <some_path> with the correct path fragment for Java and Ant installations.</some_path>
	export JAVA_HOME= <some_path>/jdk1.6.0_18</some_path>
	export ANT_HOME= <some_path>/apache-ant-1.7.0</some_path>
	export PATH=\$JAVA_HOME/bin:\$ANT_HOME/bin:\$PATH
2	Log out and log back in so that the system recognizes your changes.

Verifying the Environment Variables in Linux

To verify that environment variables have been set correctly, follow these steps:

Step	Action
	From the command line, enter:
1	echo \$JAVA_HOME echo \$ANT_HOME
	Both of these commands should return the location where you installed these tools.
2	To verify your Java SDK installation, enter <i>java -version</i> from a command prompt. You should see java version "1.6.0_18".
3	To verify your Ant installation, enter: <i>ant -version</i> from a command prompt. You should see: Apache Ant version 1.7.0 compiled on December 13 2006.

Windows

To set the environmental variables in Windows, follow these steps:



Step	Action	
1	In Windows, select Control Panel , then select the Systems application. In the Systems window, select the Advanced tab.	
2	On the Advanced tab, click the Environment Variables button. To add a new system variable , select the New button.	
	a. In the Variable <u>name</u> text box, enter JAVA_HOME .	
	b. In the Variable value text box, enter the location of your Java installation. (e.g. c:\Program Files\Java\jdk1.6.0_18)	
	Click the New button again.	
3	a. In the Variable name text box, enter ANT_HOME.	
	b. In the Variable value text box, enter the location of your Ant installation.	
	(e.g. C:\apache-ant-1.7.0).	
	Select the PATH system environment variable, and select the Edit button. This	
4		
	Edit System Variable	
	Variable value: <u>%JAVA_HOME%(bin;%ANT_HOME%(bin;</u> *	
	OK Cancel	
_	In the Variable value text box, prepend the following text in front of the text that	
5	already exists in the Variable Value field.	
	%JAVA_HOME%\bin;%ANT_HOME%\bin;	
	Click OK .	

Verifying the Environment Variables in Windows

Step	Action
	From the command line, enter:
1	echo %JAVA_HOME%
	echo %ANT_HOME%
	Both of these commands should return the location where you installed these tools.
2	To verify your Java SDK installation, enter <i>java -version</i> from a command prompt. You should see java version "1.6.0_18".
3	To verify your Ant installation, enter ant -version from a command prompt. You should see: Apache Ant version 1.7.0 compiled on December 13 2006.

To verify the environment variables have been set correctly, follow these steps:

MySQL Installation and Configuration

A MySQL 5.0.45 server must be downloaded, installed and running in order for the NBIA installation to work successfully.

To download and install MySQL, follow the steps outlined on the MySQL website: <u>http://downloads.mysql.com/archives.php?p=mysql-5.0&v=5.0.45</u>

TIP	 You should consult the following three links to successfully set up secure and well-performing MySQL servers, in preparation for installing NBIA: MySQL Security Guide - <u>http://dev.mysql.com/doc/refman/5.0/en/security-guidelines.html</u> Performance - o General performance tuning - <u>http://dev.mysql.com/books/hpmysql- excerpts/ch06.html</u>
	 InnoDB engine performance tuning - http://dev.mysql.com/doc/refman/5.0/en/innodb-tuning.html

 Record the MySQL root username/password chosen during the MySQL installation process, as you will need to use this as your database.system.user/database.system.password late in the NBIA installation process. Note the MySQL port chosen during the MySQL installation process as you will need to use this as your database.port later in the installation process. As part of the installation process, the default character set is set t latin1 for the NBIA MySQL database. 	er ss, to
--	-----------------

Once installed, you must configure My-SQL for NBIA (only for Linux).

Linux

Configure MySQL in Linux using the following steps:

Step	Action
	Lowercase Table Names in MySQL
1	Edit the /etc/init.d/mysqld (or mysql) file as follows:
	a. Locate the <pre>start()</pre> section and modify the <pre>mysqld_safe</pre> command (do not include the ellipses):
	/usr/bin/mysqld_safelower_case_table_names=1
	b. Restart the MySQL service for the changes to take effect:
	Restart /etc/init.d/mysqld

Oracle Installation and Configuration

Setting up Oracle is beyond the scope of this document. For more information, refer to http://www.oracle.com/technetwork/database/enterprise-edition/documentation/index.html.

Downloading and Installing UPT

If you do not already have a User Provisioning Tool (UPT) installed, and you wish to manage user accounts for your NBIA application, you **must** install UPT.

Overview of UPT is used to provision users in the NBIA application. Each CBIIT application installs with its own Common Security Module (CSM) schema that has sample/default users and a role/permissions structure. To add additional users, you must provision the NBIA application as "NCIA" in the UPT. Then you can assign users to NBIA.

You can download UPT 4.2 through the following link:

https://gforge.nci.nih.gov/frs/download.php/7298/CSM_UPT_42_Release.zip

For instructions on how to install UPT 4.2, refer to the chapter, UPT Installation and Deployment, in the following document.

https://gforge.nci.nih.gov/docman/view.php/12/18945/caCORE_CSM_v42_ProgrammersGuide.pdf .



Installing NBIA 5.0 Application and Services

To newly install the NBIA 5.0 application and services, follow the steps in this section:

- Downloading NBIA 5.0 files from GForge on page 9
- Installing a New NBIA 5.0 on page 10
 - o <u>GUI Installer Method</u> on page 10
 - o <u>Command-Line Method</u> on page 23
- Configuring JBoss on page 28
 - o Configuring JBoss Servers and MySQL Server to Run as Services on page 34
- Post-Installation Tasks on page 36
 - o <u>Starting Up NBIA</u> on page 36

BEFORE YOU BEGIN	 Important: There must already be a pre-existing MySQL DB and connection username/password for NBIA to install into; NBIA does not create its own DB. If you have installed a previous version of NBIA 4.5, you must follow the upgrade procedures described in <u>Upgrading NBIA 4.5 to 5.0</u> on page 29 to migrate to NBIA 5.0.
---------------------	---

Downloading NBIA 5.0 files

To download the NBIA 5.0 files, follow this step:

Step	Action
1	The installation files for NBIA 5.0 are each over 300MB. All of the files can be downloaded from the NBIA distribution folder here: <u>https://gforge.nci.nih.gov/frs/?group_id=312</u> .
	• For a new command-line installer, download the NBIA_install_5.0.zip file located here: <u>https://gforge.nci.nih.gov/frs/?group_id=312</u> .
	 For a command-line upgrade installer download the NBIA_upgrade_5.0.zip file located here: <u>https://gforge.nci.nih.gov/frs/?group_id=312</u>.
	• For a GUI installer that you can use to do a fresh NBIA 5.0 installation, download the NBIA_gui_distribution_5.0.jar located here: https://gforge.nci.nih.gov/frs/?group_id=312 .
	Remember the download location, as you will be using this file to run the installation in the steps that follow.

Server Components in NBIA 5.0

These server components are installed and configured as part of the NBIA 5.0 installation. You do not need to do anything further to download or install these components.

- - JBoss 4.0.5 (hosts the NBIA application and NBIA grid service)
 - CTP •

Installing a New NBIA 5.0

You can perform a new installation of NBIA v.5.0 using either of these two methods:

- A GUI Installation wizard. Instructions for this method begin on this page.
- A command-line installation. For instructions, see page 23.

GUI Installer Method of Installation

For detailed information on all of the GUI installer fields, refer to the documentation at this location: <u>https://wiki.nci.nih.gov/x/D6ml</u>.



If installing in Windows, double-clicking on the GUI installer jar is not recommended. Instead execute the GUI installer from the command shell. This will avoid the wrong JVM being employed to run the installer.

For performing an installation using the GUI Installer, follow these steps:

Step	Action
1	Open a command prompt in the directory where you downloaded the NBIA_gui_distribution_5_0.jar. Enter this command to invoke the GUI installer: java -jar NBIA_gui_distribution_5_0.jar.
2	The Installation Wizard opens to facilitate the installation process. Click Next to proceed through the pages of the wizard, beginning with progressing past the Welcome page. Selected screen shots are included to aid you in the installation process. Screen shot step numbers do not necessarily correspond with step numbers in these instructions.
3	Review the release notes.
4	You must accept the license agreement.
5	Select the installation type. For a new installation, select Install.

Step	Action
6	Navigate to the directory where you would like to install NBIA 5.0 using the Browse button.
	Life Sciences Distribution (LSD) 1.2 Installation Wizard: ncia Installation Folder Step 5 of 37 Select installation folder: C:\apps\ncia-lsd Browse
	If the folder does not yet exist, click OK in the dialog box to indicate that you want
7	Select the components of NBIA to be installed. To install the entire system, select Everything .
	Alternately, you can install selective components to allow them to be installed on different machines (in order to spread the load).

Step	Action	
	Configure the NBIA JBoss server on the next two pages of the installation wizard. Fields on the page are populated with sensible default values.	
8	You may want to enter and confirm your JBoss Web Console Password.	
	The port values which are specified are the defaults and can be used unless you want to reconfigure the values because the ports are already in use.	
	Refer to the publicly available JBoss user's guide at <u>www.jboss.org</u> for information about the fields on these pages.	
	🚡 Life Sciences Distribution (LSD) 1.2 Installation Wizard: ncia	
	Installation Options Step 15 of 38	
	Configure your JBoss application server	
	As part of this installation, JBoss will be installed in C:\apps\nda-bd/jboss-4.0.5.GA. It will be configured based on the values you enter below. NOTE: The Hostname below (and on other panels of this installer) is the host name accessible from this machine and others on the local network. To access this JBoss application server from the Internet, you may need to provide the JBoss HTTP Port to your Network administrator to allow access through the frewall.	
	The password you enter below is the password used to access the JBoss web console. This is a password you are creating, so you must keep track of this password for future use.	
	Setting JAVA_OPTS will override any JBoss defaults. Setting it blank will leave the JBoss default.	
	WARNING: If doing an upgrade, DO NOT specify a server name different than the server name specified earlier (for example: default). The upgrade will fail if these do not agree.	
	Hostname of this Server: INCE-KASCICE-1	
	JBoss Server Name (JBoss_HOME/server/JBoss_SERVER_INAME): default JBoss Web Console User: admin	
	18oss Web Console Password:	
	Confirm 3Boss Web Console Password:	
	JBoss Server JAVA_OPTS: i256m./tms151m.vi0X:thread3tackSze=128.v0X.5urvivorRatio=10.v5X:PermSize=128m.v5X:Max/PermSize=128 JBoss HTTP Port: 45710	
	38ost JNDI Port: 45200	
	JBoss RMI Port: 45230	
	Bioss EDBinvoker Port: 45150 Bioss COBRAD(6 not: 45280	
	38oss haydu port: 45160	
	JBoss hajmi port: 45260	
	JBoss JMS port: HS170	
	Copyright (c) 2008 National Cancer Institute - http://www.cancer.gov Previous Next Quit	
9	Specify the authentication type that NBIA should use, LDAP or database. Database is the most likely choice if you aren't sure what to select here.	
10	If LDAP was selected in the previous step, enter the appropriate configuration information for LDAP.	

Step	Action
11	Next are two pages that allow you to specify how to connect to the underlying database. The first page allows you to select whether Oracle or MySQL is to be used as the backing database.
	In the second, specify the database connection information, including the name of the pre-existing database where the NBIA schema will be installed, and the pre-existing user which will be used by NBIA to connect to its database.
	Regardless of the authentication type, the database connection parameters must be filled out. If you are installing everything or just the database, beware that all data in the specified database will be WIPED out.
	For other components (JBoss Grid, CTP), this information is just used to fill out the configuration (and won't be used to wipe anything).
	📲 Life Sciences Distribution (LSD) 1.2 Installation Wizard: ncia
	Step 19 of 38
	Consigning your PrySqL database connection The information you enter below will connect you to an existing MySQL database. Isolators is NOT a recommended value for Database hane'. It's highly recommended you contact your database administrator to obtain this information. WANNUN: If installing all components on the database collects for Database Name'. It's highly recommended you contact your database administrator to obtain this information. WANNUN: If installing all components on the database objects for Database Name'. Will be dropped and recreated during the installation process. Database Hoot Name: Isolahot Database Floots Imme: Isolahot Database Prot: Isolahot Database Prot: Isolahot Database Prot: Isolahot Database Prot: Isolahot Database Application User: Isolahot Database Application User: Isolahot Database Application User Pressword: Imment Imment Imment Database Application User Pressword: Imment
	Previous Next Quit
	Error messages inform you if the following occurs:
	• If the specified database host cannot be reached, or the field is blank.
	 If the specified database does not already exist, or the NBIA DB user's credentials are wrong.
12	Specify the SMTP mail server connection information so that NBIA can send emails from users with new account requests.

Step	Action
	Life Sciences Distribution (LSD) 1.2 Installation Wizard: ncia
13	Step 23 of 43 Configure global information for Grid configuration. Grid Index: UI: http://cagrid-index.htl.nih.gov:8080/wsrf/Services/Defaul Grid External Hot Name:
15	
	Copyright (c) 2008 National Cancer Institute - http://www.cancer.gov
	Specify the grid service index URL This will vary depending on your target grid (cagrid-index for production, cagrid-index-stage for staging).
	If the service will be behind a proxy or firewall of some kind, specify an externally- visible hostname or IP address which the index service can use to communicate with your NBIA grid service. An example indexing URL is "imaging.nci.nih.gov", and port number is "80".
	If this grid service should be configured to accept credentials to access potentially private data over https, select Yes for "Do you wish to enable grid security".

Step	Action	
	tife Sciences Distribution (LSD) 1.2 Installation Wizard: ncia Installation Options	
14	Step 24 of 43 Image: Diagram of the provided and the provide	
	Copyright (o) 2008 National Cancer Institute - http://www.cancer.gov	
	If grid security is enabled, this page allows customizing the configuration.	
	First, if the service should allow clients without credentials to retrieve public data, select "Allow anonymous access on secure grid connector".	
	Second, choose the target grid for the service. This will affect SyncGTS/GridCA and Dorian configuration. If this is a "production" level grid service, then nci_prod- xx is the likely the correct choice. If this is a test instance, the stage grid is likely a better choice.	
	Third, configure the port for the secure service and an external name/port if applicable because of a proxy/firewall, etc.	
	Finally, specify the public certificate and private key for the service. This should likely be a host certificate retrieved through GAARDS. See http://cagrid.org/display/knowledgebase/Request+a+Host+Certificate for more information on requesting a host certificate.	
	Specify the point-of-contact information needed for grid service registration. This information will span several pages of the install wizard.	
15	An error message informs you of any required fields you miss.	

Step	Action	
	Configure the JBoss grid server on the Fields on the page are populated with s	next two pages of the installation wizard. sensible default values.
	The port values which are specified are want to reconfigure the values because	e the defaults and can be used unless you e the ports are already in use.
16	Refer to the publicly available JBoss us information about the fields on these particular	ser's guide at <u>www.jboss.org</u> for ages.
	if Life Sciences Distribution (LSD) 1.2 Installation Wizard: ncia Installation Options	
	Step 29 of 43	
	Configure your JBoss application server for the (NBIA co	re) grid service
	As part of this installation, JBoss will be installed in C: lapos/inda-6 below. NOTE: The Hostname below (and on other panels of this in access this JBoss application server from the Internet, you may no the firewall.	d/ncia-core-grid/jboss-4.0.5.GA. It will be configured based on the values you enter staller) is the host name accesible from this machine and others on the local network. To sed to provide the JBoss HTTP Port to your Network administrator to allow access through
	The password you enter below is the password used to access the password for future use.	: JBoss web console. This is a password you are creating, so you must keep track of this
	Setting JAVA_OPTS will override any JBoss defaults. Setting it bla	nk will leave the JBoss default.
	WARNING: If doing an upgrade, DO NOT specify a server name d if these do not agree.	fferent than the server name specified earlier (for example: default). The upgrade will fail
	Hostname of this Server:	NCI-01738905
	JBoss Server Name (JBoss_HOME/server/JBoss_SERVER_NAME):	default
	JBoss Web Console User:	admin
	JBoss Web Console Password:	******
	Confirm JBoss Web Console Password:	2000 Verifitar VV.TerredCard/Care-120, VV.C.m.SurData-10, VV.DerreCare-120, VV.Mer/DerreCare-120
	IBoss Server JAVA_OPTS:	223011 -ANX31201 -AX111/2803(80/3/28=128 -AX150/10/07R800=10 -AX192/115128=12811 -AX198/28115128=128
	Boss INDI Port	21200
	JBoss RMI Port:	21230
	JBoss EJBInvoker Port:	21150
	JBoss CORBAORG port:	21280
	JBoss hajndi port:	21160
	JBoss hajrmi port:	21260
	JBoss JMS port:	21170
	Copyright (c) 2008 National Cancer Institute - http://www.cancer.gov	
	Copyright by Copinational values institute - inspiritum cancer gov	Previous Next Quit

Step	Action	
17	In addition to the JBoss ports for the grid server, this page allows specifying a temporary directory for zipping DICOM files. The directory that is specified should be on a partition that has plenty of space.	
	Life Sciences Distribution (LSD) 1.2 Installation Wizard: ncia	
	Installation Options	
	Additional JBoss (for grid service) installation options	
	JBoss jmx+mi port: 21290 JBoss messaging port: 21330 JBoss pooledha port: 21270 JBoss remoting port: 21320 JBoss redirect port: 21320 JBoss rmiobject port: 21220 JBoss smitoport: 21220 JBoss somp-trapd port: 21240 JBoss somp-trapd port: 21300 JBoss solid port: 21250 Temp directory for zipping grid transfers: /tmp/tempzip The host and port MUST match the JBoss public URL (where the webapp is installed). URL to the thumbnail server on appserver.: http://NCI-01738905:45210/ncia/publicThumbnails 1	
	Copyright (c) 2008 National Cancer Institute - http://www.cancer.gov	

Step	Action
	Specify the runtime variables for NBIA. For detailed descriptions on each of the properties, see the Application Settings at https://wiki.nci.nih.gov/x/D6ml
	🔐 Life Sciences Distribution (LSD) 1.2 Installation Wizard: ncia
	Installation Options
18	Step 31 of 43
	For detailed descriptions on each of the properties below, see the Application Settings section at https://wiki.ndi.nih.gov/x/koQYAQ
	NBIA Zip File Location: /var/ftp/ncia
	NBIA UID Display Length: 100
	NBLA Site Name: Other
	Boss public URL: Ittp://NCI-01738905-45210/ncia/
	Download Server URL: wwnload/servlet/DownloadServlet
	Enable public search access (relies upon guest account)
	Public Search guest username: htia_guest
	Registration Email Subject Line: User registration to access the National Biomedical Imaging Archive (NBIA)
	If FTP/HTTP download is NOT enabled, then the values for FTP host name and location are not important.
	NBIA FTP Host Name: localhost
	NBIA FTP Location: /var/ftp/ncia
	The value for the Local Name should match the grid research center display name property.
	NBIA Grid Node Local Name: NCI-CBIIT-QA
	DO NOT use localhost here. Enter the actual proxy/host name or IP address where the grid server is being installed.
	NBIA Grid Node Local URL: [http://NCI-01738905:21080/wsrf/services/cagrid/NCIACoreService
	Convricht (c) 2008 National Cancer Institute - http://www.cancer.gov
	Previous Next Quit

Step	Action	
	Specify the configuration for the CTP (Clinical Trial Processor) Server.	
19	 King user is a superadmin that has the privilege to shutdown the CTP server and others. 	
	 Admin user has all the privileges of king without the privilege to shutdown the server. 	
	WARNING: Please be sure to select a "Directory for Storage Service" that is outside of the NBIA installation directory. This will ease future upgrades.	
	Life Sciences Distribution (LSD) 1.2 Installation Wizard: ncia Installation Options Stan 29 of 40	
	CTP Server Configuration	
	CTP Server HTTP port: 23080 CTP HTTP Import Service port: 23104 CTP Server Storage Service port: 23304 CTP Server Admin Password: * Confirm Password: * Confirm Password: * CTP Server King Password: * Confirm Password: * Directory for Storage Service: storage Index directory for Storage Service: index Require authentication on Import Service	
	Specify the configuration for the CTP (Clinical Trial Processor) Client.	
	Installation Options	
20	CTP Client Configuration	
	CTP Client HTTP port: 24080	
	CIP Client HTP Import Service port: 24104 CIP Client DICOM Import Service port: 24304	
	CTP Client Export Service port: 24204	
	Confirm Password:	
	CTP Server King Password: Confirm Password:	
21	To display a logo in the NBIA application's header select Yes .	

Step	Action	
22	Select two image files on the local system: one for the logo, and one for the background to be displayed behind the logo. The logo should be 300x20 or else it will be distorted. Both of these fields must have values.	
	Installation Options Step 24 of 29	
	Optional Branding Optionally, select a 300x20 JPG, GIF, or PNG as a logo for the application. Not selecting an image of the proper dimensions will cause distortion. Branding Logo: Browse Optionally, select a JPG, GIF, or PNG as a background for the logo. This image can be any size.	
	Branding Logo Background: Browse	
23	The NBIA Download Manager requires that the jar files that constitute it be digitally signed. There is an option to let the installer generate a "self-signed" certificate. Alternately, if there is an existing (organization) certificate, that can be used.	
	To auto-generate the certificate, select Yes .	
24	If you opt to auto-generate the certificate, you can specify on this page where the keystore will be created. It also allows you to specify the alias of the key to be created.	
	Life Sciences Distribution (LSD) 1.2 Installation Wizard: ncia Installation Options Step 34 of 38	
	These fields will CREATE a keystore to use for signing. NOTE: the directory you specify MUST exist in order for the keystore to be created there. NOTE: do not create the keystore as the file c:/tmp/ncia or it will cause the install to fail. Keystore file location: c:/keystore Keystore file password: ********* Confirm keystore file password: ********* Keystore alias: nbia_dl_mgr_cert	

25 If you opt to use an existing certificate, you can spect keystore is (already) located. Life Sciences Distribution (LSD) 1.2 Installation Wizard: ncia Installation Options Step 33 of 38 These fields point to an EXISTING keystore. Keystore file location: c:/keystore1	ify on this page where the	
These fields point to an EXISTING keystore.	Browse	
Keystore alias: nbia_dl_mgr_cert Keystore file password: ************************************		
 Review the selected install type and the installation of After you click Next from reviewing the installation de The installation wizard displays the installation program 	Review the selected install type and the installation destination. After you click Next from reviewing the installation destination, the installer runs. The installation wizard displays the installation progress and completion.	
27 When you are informed that the process is finished, of corner of the wizard to close the installer.	When you are informed that the process is finished, click Done in the lower right corner of the wizard to close the installer.	
28 To verify NBIA installation: • Open your web browser to <u>http://<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:<jboss.server.hostname>:</jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></jboss.server.hostname></u>	<pre>To verify NBIA installation: Open your web browser to <u>http://<jboss.server.hostname>:<jboss.server.port>/ncia</jboss.server.port></jboss.server.hostname></u> (example; <u>http://hostname.com:45210/ncia</u> Refer to the <user home="">/.installer- NCIA/NCIA_installer/install.properties file for the correct values.</user></pre>	

29	To verify that the NBIA Grid Service is up and running:		
	 Check that NBIA Grid Service appears on the local "services" page. Point a browser to the "services" page. The URL for this page is http://host:port/wsrf/services. Examine the page and ensure that "cagrid/NCIACoreService" appears on the page. Select the "wsdl" link next to "cagrid/NCIACoreService". Examine the WSDL and check that the host and port in the //wsdl:import@location attribute are correct. Examine the WSDL and check that the host and port in //soap:address@location attribute are correct. Check that the NBIA Grid Service appears on the caGrid Portal. 		
30	After successfully installing NBIA, make a backup of the <user home>/.installer-NCIA/NCIA_installer/install.properties file in a different directory for future reference.</user 		

Installing NBIA One Component at a Time

	 When installing NBIA one component at a time, be aware of the following: The configuration parameters must agree across the components. 	
Important	 A few examples: 1. All of the components should share the same database connection parameters. 2. The grid component must communicate with the JBoss web application so the JBoss host and port must agree between these two components. 3. The JBoss and database components both require configuration information about the guest account. These must agree. 	
	 Strictly speaking, there is not a rigid order in which the components must be installed. However, the database is likely the first thing to install since the installer will try to start all the other components and if the database is not there, the servers will show errors upon starting. These servers must be restarted after the database is installed. The installer pages for the individual components are, for the most part, the same pages that are used when installing "Everything" so the documentation for the "Everything" path should largely apply. 	

Command-Line Method of Installation

About Properties

An important component of NBIA 5.0 command-line installation is configuring properties.

Overview of NBIA 5.0 Command-Line Installer Properties Files	When you do a command-line installation of NBIA 5.0 for the first time, you will work with the install.properties file included in the NBIA_install_5_0.zip.
	If you are using the command-line to upgrade from the previous version of NBIA 4.5, you will work with the upgrade.properties file included in the NBIA_upgrade_5_0.zip. For more information about upgrading NBIA, see Upgrade Using Command-Line Installer on page 30.
Overview of Properties Files	When you installed the previous version of NBIA 4.5, you configured the install.properties. The NBIA_upgrade_5_0.zip that you must download to perform the upgrade to 5.0 includes another properties file, upgrade.properties. To complete the upgrade to NBIA 5.0, you should use the values in the install.properties to configure values in the upgrade installer wizard GUI, or the upgrade.properties file if you are doing a command-line method of upgrade.

See the steps below for more information.

In several instances in this section, property values must be modified. Note the following points about changing or entering variables.

Paths in .properties Files

NOTE	The paths in the .properties files should use <i>forward</i> slashes. For example, you would use application.base.path.window=C:/apps/NBIA, not application.base.path.window=C:\apps\NBIA. If you use backslashes, you will experience undesirable results.
------	--

Spaces in Property Values



You should not put any spaces in the property values of *.properties files (e.g. install.properties). In Windows, note that the C:\Documents and Settings\<*username*> path contains spaces and the installation will likely fail. If you are using Windows, use a path such as C:/apps/NBIA.

More About Property Values

	• In the install.properties and the upgrade.properties files, any property value marked with <u>uppercase</u> REPLACE_* must be manually updated with the appropriate value.
NOTES	• In each *.properties file, any property value marked with <u>lowercase</u> replace_* may be optionally updated with the appropriate value.
	• In many of the steps below, there is reference to a database.system.user for your MySQL server. To determine which users are have full privileges to create and manage other databases, type <i>show grants</i> from a MySQL prompt to determine the correct level of privileges.

NBIA Port Usage

NOTE Verify that default port values defined in install.properties and upgrade.properties files are not in use on your system by running netstat -a from the command line. If the ports are in use prior to installation, you will likely experience problems with your installation.	
---	--

JBoss Errors During Installation

NOTE	You may receive an error such as Exception in thread "main" java.lang.NoClassDefFoundError: org/jboss/Shutdown. This should not be a problem, as the installer attempts to remove previously installed servers to prevent problems during the installation. If this is your first time installing NBIA, you may receive and disregard this error message.
------	--

Command-line Installation Steps

To install a new instance of NBIA 5.0 using the command-line, follow these steps:

Step	Action		
1	From the directory where you downloaded the NBIA_install_5_0.zip from <u>Downloading NBIA 5.0 files</u> on page 9, unzip the files, using one of these two methods:		
	a. Open a command prompt and use it to extract this file to a temporary location. For example, you may enter a command such as unzip -q NBIA_install_5_0.zip (you must have a ZIP tool installed). This location will be referred to as the <installer_directory> henceforth.</installer_directory>		
	b. Use WinZip or a similar utility to unzip the files to a temporary location. location will be referred to as the <installer_directory> hencefor</installer_directory>		
	<pre>Example: <installer directory=""> = C:\NBIA_5_0_installer</installer></pre>		
2	Note: Setting the property values is an important step in the install process. Before you complete steps 2 & 3, review <u>About Properties</u> on page 23. Follow steps 2 and 3 carefully .		
Open the <installer_directory>/install.properties file, mo values for your environment and save the file. At a minimum, you will ne modify the values in the following table. For detailed information on all of the properties, refer to the documentati location: https://wiki.nci.nih.gov/x/D6ml.</installer_directory>		Ty>/install.properties file, modify the ve the file. At a minimum, you will need to able. e properties, refer to the documentation at this <u>6ml</u> .	
	Property Name	Description	
	application.base.path	The location where you are going to install NBIA. For example in Windows, the <application_base_path> can be C:/apps/NBIA. Linux users can use /apps/NBIA or any other folder to which you have write permissions.</application_base_path>	
	database.type	This may be 'oracle' or 'mysql'	
	database.system.user	This value should correspond to a MySQL username that has full system privileges. This must correspond to the administrator account defined when MySQL was configured. See the first bullet in More Tips on page 7.	
		For Oracle, this value will be ignored, but the value must be different than the value of database.user.	
	database.system.password	This value <u>must</u> correspond to the password for the database.system.user defined when MySQL was configured. See the first bullet in More Tips on page 7.	

Step	Action		
		For Oracle, this value will be ignored.	
	database.server	This value <u>must</u> correspond to the domain name of machine that hosts the database server. Talk to your database administrator to learn the server name and port.	
	database.port	This value <u>must</u> correspond to the port for the database.server. 3306 is the default port, but check with your database administrator to be certain.	
	database.name	Choose a name for the NBIA database. This must be different than the UPT database name.	
	database.user	Choose a user name to access database.name. This can be any valid name that you choose, but it must be different than database.system.user.	
	database.password	Choose a password to access database.name for the username identified in database.user. This must be different than the database.system.password.	
	mail.smtp.server	This value <u>must</u> correspond to an SMTP server available in your network. This will differ in your environment. Consult your email administrator for the SMPT server and port (next value).	
	grid.index.url	The default value points to the production grid index server. To change to a different grid index, uncomment the desired one while commenting-out the production value.	
	jboss.web.password	Set to a secure password to be used to secure the NBIA JBoss server's administrative functions (e.g, admin console, JMX console, command-line shutdown of JBoss server, etc.)	
	authentication.type	This value (Idap/db) indicates to use either LDAP or Database to authenticate users. This determines whether passwords will be stored in the NBIA database or in an external LDAP server. Most sites will likely set this to 'db'.	
	research.center.displayN ame	Set this value to the full name of the research center which is hosting the NBIA installation. This value will show in the caGrid Portal application (as will the other research.center.* property values).	

Step	Action	
	research.center.shortNam e	Set this value to the short name, or initials, for the research institution which is hosting the NBIA installation.
	research.center.address. country	Set this value to the name of the country where the research institution which is hosting the NBIA installation resides.
	research.center.address. locality	Set this value to the name of the locality where the research institution which is hosting the NBIA installation resides.
	research.center.address. postalCode	Set this value to the postal code where the research institution which is hosting the NBIA installation resides.
	research.center.address. stateProvince	Set this value to the name of the state or province where the research institution which is hosting the NBIA installation resides.
	research.center.address. street1	Set this value to the street address of the research institution which is hosting the NBIA installation.
	point.of.contact.affilia tion	Set this value to the name of the institution with which the primary point of contact for the NBIA installation is affiliated.
	point.of.contact.email	Set this value to the email address of the primary point of contact for the NBIA installation.
	<pre>point.of.contact.firstNa me</pre>	Set this value to the first name of the primary point of contact for the NBIA installation.
	<pre>point.of.contact.lastNam e</pre>	Set this value to the last name of the primary point of contact for the NBIA installation.
	point.of.contact.phoneNu mber	Set this value to the phone number of the primary point of contact for the NBIA installation.
	point.of.contact.role	Set this value to the role of the primary point of contact for the NBIA installation.

Step	Action		
	gov.nih.nci.NBIA.imaging .server.url	URL for image server location. An example of this URL would be:	
		http://imaging.nci.nih.gov.	
		This should be the protocol scheme combined with the public domain name for the host where the application server is running. This will usually be the actual domain name for the host, but if there is a proxy, the name may be different.	
		If this is not set correctly, then thumbnail views on the "series page" will not show.	
	gov.nih.nci.NBIA.grid.lo cal.node.name	Required Identification of the local instance of NBIA.	
	gov.nih.nci.NBIA.ui.uid. display.length	This property will determine the maximum length for DICOM UID values in the user interface. Any UID longer than this value will be truncated with a trailing ellipsis.	
	gov.nih.nci.NBIA.jboss.m q.url	The value of this property should ALWAYS be "localhost: <port>" where <port> have the exact same value as \${jboss.server.jndi.port}.</port></port>	
		If this is not configured properly curation upload and the zipping of DICOM image files for download will not work properly.	
	gov.nih.nci.NBIA.admin.e mail	The email address of the NBIA administrator	
	ctp.server.admin.passwor d	Administration password for CTP server	
	ctp.client.admin.passwor d	Administration password for CTP client	
	gov.nih.nci.NBIA.jboss.p ublic.url	Public accessible url for NBIA instance.	
	Record these property values.		
3	Note: You should not need to modify the other default values as we have chosen unique ports to reduce the risk of other applications using the same values. However, be sure to verify that the ports in this file are not being used by other applications.		
4	From the command line, navigate to <installer_directory> (<i>Example</i>:cd C:\NBIA_5_0_installer), and type <i>ant</i>. This initiates the installation process. The anticipated duration is anywhere from 7-15 minutes, depending on your system's speed, power and memory.</installer_directory>		
	The installer installs the NBIA schema in the specified pre-existing database on your MySQL server, and installs, configures, and starts the JBoss server and the Tomcat server for the grid service. The installer does not currently start the CTP server.		

Step	Action
5	To verify NBIA installation, open your web browser to <u>http://<jboss.server.hostname>:<jboss.server.port>/ncia</jboss.server.port></jboss.server.hostname></u> (example; <u>http://hostname.com:45210/ncia</u> "Refer to the <installer_directory>/install.properties file for the correct values. Enter <i>nciadevtest</i> as the user and <i>changeme</i> as the password.</installer_directory>
6	After successfully installing NBIA, make a backup of the <pre><installer_directory>/install.properties file in a different directory for future reference.</installer_directory></pre>

Upgrading NBIA 4.5 to 5.0

This section describes how to upgrade your product from NBIA 4.5 to NBIA 5.0. The instructions in this section apply only if you have already installed NBIA version 4.5.x.

You can perform an upgrade installation of NBIA v.5.0 using either of these two methods:

- A GUI Installation wizard. Instructions for this method begin on this page.
- A command-line installation. For instructions, see page 32.

Before You Begin	• Important: Backup the 4.5 database. You need to create a reliable copy of your entire NBIA database—the DDL and DML.
	• Important: Backup the jboss.home directory. To do this, make a copy of the NBIA.home folder along with any artifacts from the initial installation, such as the property files, already mentioned.
	• Important: You cannot upgrade from NBIA with MySQL to a new NBIA that uses Oracle. You must install a fresh NBIA with Oracle and migrate the data manually. This whole section assumes you are upgrading from MySQL (to NBIA 5.0 with MySQL) since that is the only database that was supported by NBIA 4.5. Please contact NCICB application support if you require help with migration.

If you are performing a new installation, go directly to the installation of version 5.0, <u>Installing</u> <u>NBIA 5.0 Application and Services</u>, on page 8.

	• The directions in this section presume that you have a valid and functioning NBIA 4.5. That assumes that Java SDK, Apache Ant and MySQL have all been successfully uploaded and installed, as described on page 3 in this document.
NBIA 4.5 Users Upgrading to NBIA 5.0	• The upgrade to NBIA 5.0 adds new constraints to the data model. This is done in order to stop erroneous submissions from happening. If such submissions have already occurred, there may already be duplicate or corrupt data in the database. The upgrade will fail in such a case, and

the corrupt data needs to be cleaned out before the upgrade can be successful.

Upgrading NBIA Using the GUI Installer

For detailed information on all of the GUI installer fields, refer to the documentation at this location: <u>https://wiki.nci.nih.gov/x/koQYAQ</u>.

To perform an upgrade to NBIA 5.0 using the GUI Installation Wizard, follow these steps:

Step	Action
1	Open a command prompt in the directory where you downloaded the NBIA_gui_distribution_5_0.jar and invoke the GUI installer like this: java -jar NBIA_gui_distribution_5_0.jar.
2	The Installation Wizard opens to facilitate the installation process. Click Next to proceed through the pages of the wizard, beginning with progressing past the Welcome page. Screen shots are included where helpful.
3	Review the release notes.
4	You must accept the license agreement to continue.
5	Select the Upgrade installation type.
6	Select the components of NBIA to upgrade. To upgrade the entire system, select Everything .
Ĵ	Alternately, selective components can be upgraded per machine.

Step	Action
	Select the location for the previous installation. If the path pointing to the NBIA installation to be upgraded is incorrect, an error message appears.
7	Life Sciences Distribution (LSD) 1.2 Installation Wizard: ncia Installation Options Step 7 of 38
	Existing Locations Application Root Directory: c:/apps/ncia Browse
	For each JBoss container, the upgrader requests the server name to upgrade.
8	Installation Options Step 8 of 38
	Existing Locations Notional O JBoss Server name:
	The installer software now inspects the application base path to determine the
9	existing configuration (the best that it can), and the install wizard registers this action.

Step	Action
10	From here on, the upgrade process looks almost exactly like the install process, described starting on page 10 in this document. The installer software has populated the defaults for all fields from the existing installation the best that it can. For fields that are new in this release, there are sensible defaults.

Overview of Properties Files When you installed the previous version of NBIA 4.5, you configured the install.properties. The NBIA_upgrade_5_0.zip that you must download to perform the upgrade to 5.0 includes another properties file, upgrade.properties. To complete the upgrade to NBIA 5.0, you must use values in the install.properties to configure values in the upgrade installer wizard GUI, or the upgrade.properties file if you are doing a command-line method of upgrade.

See the steps below for more information.

Upgrading NBIA Using Command-Line Installer

To perform an upgrade to NBIA 5.0 using the command-line, follow these steps.

Step	Action
1	From the directory where you downloaded the upgrade zip file, extract the files, using one of these two methods:
	a. Open a command prompt and use it to extract this file to a temporary location. For example, you may enter a command such as unzip -q NBIA_upgrade_5_0.zip. (You must have a ZIP tool installed).
	Note: It is recommended that you use a new directory for the unzipped files, rather than the one you used to unzip the installer for the previous version(s) of NBIA. This location will be referred to as the <upgrade_installer_directory> henceforth.</upgrade_installer_directory>
	 Use WinZip or a similar utility to unzip the files to a temporary location. This location will be referred to as the <upgrade_installer directory=""> henceforth</upgrade_installer>
	<pre>Example <upgrade_installer directory=""> = C:\NBIA41_upgrade_installer</upgrade_installer></pre>

Step	Action
2	Edit the default properties in the <upgrade_installer_directory>/ upgrade.properties file. To do so, open both properties files, the one you configured originally when you installed the previous version of NBIA 4.5.x. (<install.properties file="">) and the <upgrade_installer_directory>/ upgrade.properties file.</upgrade_installer_directory></install.properties></upgrade_installer_directory>
	Note: Where there are duplicate attributes, the values must be the same in both files.
	Copy each entry you modified in the 5.0 installation file and paste it in the corresponding location in the upgrade.properties file, replacing the default text, as appropriate. All the properties that appear in upgrade.properties appear in install.properties (but not vice versa). Consult the Command-Line Method of Installation of this guide on page 23 for more background on the meaning of the properties.
	Record these property values.
3	Note: You should not need to modify the other default values as we have chosen unique ports to reduce the risk of other applications using the same values. However, be sure to check the *.properties to verify that the ports in this file are not being used by other applications.
4	From the command line, navigate to <upgrade_installer_directory>/ (<i>Example</i>:cd C:\NBIA42_upgrade_installer), and type <i>ant</i>. This initiates the upgrade process. The anticipated duration is anywhere 7-15 minutes depending on your system's speed, power and memory.</upgrade_installer_directory>
	The installer upgrades your existing NBIA database on your MySQL server, starts your existing JBoss servers and starts up the grid service for the NBIA application.
	Notes regarding upgrade:
	When the installer detects that a database exists, it warns you to back it up, which you were instructed to do earlier in this process. Press Y to proceed.
5	To verify NBIA installation, open your web browser to http:// <jboss.server.hostname>:<jboss.server.port>/ncia (example: http http://hostname.com:45210/ncia) and enter <i>nciadevtest</i> as the user and <i>changeme</i> as the password. Refer to the original install.properties for the correct jboss.server.hostname and jboss.server.port values.</jboss.server.port></jboss.server.hostname>

Configuring JBoss



For optimal performance, you must modify your JBoss 4.0.5 configuration to increase the amount of available memory for the NBIA application. Directions for doing this in Windows are in the following step 1.

To configure JBoss in Windows, follow these steps:

Step	Action
1	Add the following entry to the JBoss run.bat file which is located will be located at <application_root_directory>/jboss-4.0.5.GA/bin/run.bat. Add the text right after the line "rem Add -server to the JVM options, if supported".</application_root_directory>
	-server -Xms1024m -Xmx1024m -XX:ThreadStackSize=128 - XX:SurvivorRatio=10 -XX:PermSize=128m -XX:MaxPermSize=128m - Dsun.rmi.dgc.client.gcInterval=3600000 - Dsun.rmi.dgc.server.gcInterval=3600000 - Djava.awt.headless=true
	Warning : Be careful when copying and pasting from this document, whether PDF or MS Word. No spaces must come before and after the columns. A safe way to ensure that the text has no unwanted space and unwanted characters is to copy the text into a blank text editor such as NotePad first. Correct the spacing, then copy and paste back into the run.bat file.
2	Restart your JBoss 4.0.5 server for the changes to take effect. The method of doing this may depend on the start/stop/restart scripts you created after the installation. Most commonly, you can execute shutdown.bat and then run.bat under \$JBOSS_HOME/bin. Refer to the publicly available JBoss user's guide at www.jboss.org for more information.

Configuring JBoss Servers and MySQL Server to Run as Services

NOTE	MySQL, and the two JBoss servers that make up NBIA, and the JBoss server optionally installed for UPT, must run continually as services. The instructions in this section cover all of these scenarios. For a NBIA 5.0 deployment, there are at least four servers, and if UPT is installed, five servers:
	JBoss 4.0.5 (for NBIA application and grid service)
	• MySQL 5.0.27
	CTP (Clinical Trial Processor)



The default NBIA installation runs JBoss as a command line process using the user currently logged on. Therefore, when you log out as this user, JBoss is no longer available for NBIA. For that reason, it is recommended that you configure your JBoss servers to run as a Linux or Windows service. The instructions are contained in this section.

To run JBoss as a service, follow these steps:

Step	Action
	Linux
1	See http://wiki.jboss.org/wiki/Wiki.jsp?page=StartJBossOnBootWithLinux .
	Windows
2	To run an existing JBoss command line installation as a service, follow the directions for creating a user-defined service at http://support.microsoft.com/kb/137890/EN-US/
	Note: You must have access to the Windows Resource Kit.

Running MySQL as a Service

NOTE It is assumed that your MySQL server was installed as a service. If it was not, follow these recommendations for installing this server as a service.		NOTE	It is assumed that your MySQL server was installed as a service. If it was not, follow these recommendations for installing this server as a service.
--	--	------	---

To run MySQL as a service, follow these steps:

Step	Action
	Linux
1	
	See http://www.redhat.com/docs/manuals/enterprise/RHEL-AS-2.1-
	Manual/cluster-manager/s1-service-mysql.html.

Step	Action
	Windows
2	
	When installing MySQL server on Windows, choose the option to run MySQL as a Windows service.

Post-Installation Tasks

Starting Up

NBIA

Note that if JBoss and CTP are not installed as services, they must be manually started/re-started. The following files will start the respective servers.

On Windows:

- JBoss: ncia/jboss-4.0.5.ga/bin/run.bat
- Grid JBoss: ncia/ncia-core-grid/jboss-4.0.5.ga/bin/startup.bat
- CTP: ncia/CTP-server/CTP/ctp.bat

On Linux:

- JBoss: ncia/jboss-4.0.5.ga/bin/run.sh
- Tomcat: ncia/ncia-core-grid/jboss-4.0.5.ga/bin/startup.sh
- CTP: ncia/CTP-server/CTP/ctp.sh

Using UPT to Add NBIA Users



To use the UPT, follow these steps:

Step	Action
1	Install UPT.
2	Launch a browser and access UPT via value of application.url (from UPT's install.properties).

Step	Action
	Log in to UPT, using the following profile:
3	• Login ID=superadmin
	Password=changeme Application Nome
	• Application Name=csmupt
4	Select the User tab at the top of the page, and click Create a New User .
5	Enter Login Name, User First Name, User Last Name, User Password, User Password Confirm. Click Add.
6	On the Application tab at the top of the screen, click Create a New Application .
	Enter the following parameters:
7	Application Name= <i>NCIA</i>
	 Application Description=<application description=""></application>
	Application Declarative Flag= <i>Yes</i>
	Application Active Flag= <i>Yes</i>
	Application Database
	URL=jdbc:mysql://\${database.server}:\${database.port}/\${NB IA.database.name}
	 Application Database User Name=\${NBIA.database.user}
	Application Database User Password=
	\${NBIA.database.password}
	Application Database Confirm Password=
	\${NBIA.database.password}
	• Application Database Dialect=org.hibernate.dialect.MySQLDialect
	Application Database Driver=com.mysql.jdbc.Driver
	When you provision the application in UPT 4.2, you are asked to specify the CSM version NBIA is using. You should enter v. 4.0.
	NOTE: \${NBIA.xxxx} should be interpreted as the value of property xxxx when NBIA was installed (as opposed to any UPT installation property value)
8	Click on Add > Associated Admins. then click on Assign Admin.
9	Highlight the user you want to be admin of the application, and click Assign Admin .
10	Log out of UPT.

Step	Action
11	Log in to UPT (from UPT's install.properties). Use the following login profile:
	• Login ID= <user above="" created=""></user>
	• Password= <password above="" created="" for="" user=""></password>
	Application Name=NCIA
12	Add users to the NBIA application as you did above.
13	Click Logout.

Contacting Application Support

NCICBhttp://ncicb.nci.nih.gov/NCICB/supportApplicationTelephone: 301-451-4384SupportToll free: 888-478-4423